



BITUMEN SPRAYER (Trolley Mounted)



BITUMEN SPRAYER (TROLLEY MOUNTED)



BITUMEN SPRAYER TECHNICAL DETAILS

Tank Capacity	:	3000 Liters
Tank Insulation	:	50 mm Cera Wool
Prime Mover	:	Diesel Engine, 'Kirloskar' make, 16 HP @ 1500 RPM, Air-Cooled, Twin Cylinder
Burner	:	Automatic (Auto Firing, Auto CUT OFF / ON at preset temperature.)
Pump	:	High Pressure, Positive Displacement type Internal Gear Pump
Flow Control Valve	:	1½" 3 Way Valve
Air Compressor	:	2 HP
Hand Spray Bar	:	Single Nozzle, 1 mtr. Bar with 5 mtrs. Flexible Hose
Fix Spray bar	:	2750 mm Length with 12 Nos. Spraying Nozzles (6 LPM each)
Thermometer	:	Dial Type 0 - 300° C and Digital in panel

NOTE: Manufacturer reserves the right to change above specifications without prior notice in order to improvement or modifications.

Application : Bitumen Sprayer used for tack coat and seal coat.

Features : Tractor Towable Trolley type Bitumen Sprayer
Suitable for Bitumen & Emulsion spraying.
Auto fired burner for fuel efficiency & maintaining bitumen quality.
Imported Bitumen Pump.



CAPIOUS ROADTECH PVT LTD.

An ISO 9001 : 2015 Company

Government of India Recognized One Star Export House

www.capious.com

Plot#4008, Phase IV, Road No. R4, Nr. Nika Tube Cross Road, G.I.D.C., Vatva Industrial Estate, Ahmedabad 382 445,

Gujarat, India **Ph.:** +91 79 40083274, 25833436, 25890356, **M:** +91 96876 18093 **Fax:** +91 79 40083274, 25833597 **Email:** info@capious.com